


Car-Go_s 200 | 10 W | diffuse | Floor recessed

Drive over 2000 Kg | 20 km/h

Technical Specifications

Source lamp	LED 10 W
Total wattage	10
Voltage	24 Vdc
Control	Power supply not included
Luminous flux (*Source flux)	474 lm (1470 lm*) @ 3000 K
Luminous efficacy	50 lm/W @ 3000 K
McADAM steps	3
Beam	diffuse
CRI	>90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	67
IK rating	10
Insulation class	III



Materials

Body	Extruded aluminium EN AW6026
Diffuser	Opal glass
Finishing	White - Glass

E (lux)

H(m)	lux(3000 K)	Ø(m)
1.00	141	4.26
2.00	35	8.52
3.00	17	12.77
4.00	10	17.03
5.00	6	21.29

Included accessories

-	0.5 m length cable -05RN-F
-	Housing box

Available accessories

0303004	Glass lifting suction pad
00KCGQ.04	Recessed box adjusting kit
0404M011	Single connection IP68
0404M019	Three-way connection box mini
0409BT016	Transformer _ 24 Vdc - 100 W (connect up to 8 pcs)
0409BT015	Transformer _ 24 Vdc - 25 W (connect up to 2 pcs)