Cod: DV60120DHB103


Duvali | 5.5 W | diffuse | Bollards

120 cm

Technical Specifications

Source lamp	LED 5.5 W
Total wattage	8
Voltage	220-240 Vac - 50/60 Hz
Control	On/Off
Luminous flux (*Source flux)	542 lm (759 lm*) @ 3000 K
Luminous efficacy	68 lm/W @ 3000 K
McADAM steps	3
Beam	diffuse
CRI	>90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	65
IK rating	8
Insulation class	II








Materials


Body	Accoya® wood and inox AISI 316L
Diffuser	Opal polycarbonate
Finishing	Accoya® - Acetylation treatment

LANDA ILLUMINOTECNICA S.p.A. - Via Rosmini, 13/15 - 25065 Lumezzane – Brescia – Italy - T +39 030 892 0966 - F +39 030 892 1003 - www.landa.it - E info@landa.it - P.IVA IT00688140987 - CF 02125310173
All right reserved Landa illuminotecnica S.p.A. will reserve to change the specific note without any written notice

Isolux



Photometry



Included accessories

--	Root mounting kit
-	Single connection IP68

All right reserved Landa illuminotecnica S.p.A. will reserve to change the specific note without any written notice